

Rose Jo Morton

Finished Size: 691/2"x691/2" Moda Web Pattern 38120

CUTTING.

Fabric 1......1³/₄ yds.

Cut: 6 –6"xWOF strips.

From the strips cut a total of 36-6"x6" squares. Cut squares once diagonally to make 72-half square triangles for 9-Patch block corners. Cut: 7 –2⁵/₈"xWOF strips for 9-Patch blocks.

Fabric 2.....1³/₄ yds. Cut: 6 –6"xWOF strips.

From the strips cut a total of 36-6"x6" squares. Cut squares once diagonally to make 72-half square triangles for 9-Patch block corners. Cut: 7 –2⁵/₈"xWOF strips for 9-Patch blocks.

Fabric 3......³/₄ yd.

Cut: 8 –2⁵/₈"xWOF strips for 9-Patch blocks.

Cut-2¹/₂" bias strips to equal 300 inches. Approximately 8-10 strips.

Fabric 5.....¹/₂ yd.

Cut: 5 –2"xWOF strips From the strips cut a 96-2"x 2"squares for Sashing Units 2 and 3 triangles. Cut: $1 - 3\frac{1}{2}$ "xWOF strip. From the strip cut 5-3¹/₂"x 3¹/₂"squares for sashing star centers.

Fabric 6.....11/2 yds. Cut: 8 –2⁵/₈"xWOF strips for 9-Patch blocks. Cut: $5 - 3\frac{1}{2}$ "xWOF strips. From the strip cut 52-3¹/₂"x 3¹/₂"squares for sashing corners.

Fabric 7.....¹/₂ yd.

Cut: 5 –2"xWOF strips From the strips cut a total of 104-2"x 2"squares. for Sashing Units 1 and 3 corner triangles. Cut: $1 - 3\frac{1}{2}$ "xWOF strip. From the strip cut 8-3¹/₂"x 3¹/₂"squares for sashing star centers.

Fabric 8.....15% yds. Cut: 5 –2"xWOF strips

From the strips cut a 104-2"x 2"squares for Sashing Units 1 and 3 corner triangles.

Cut: $12 - 3\frac{1}{2}$ "xWOF strips. From the first strip cut 12-3¹/₂"x 3¹/₂"squares for sashing star centers. From the remaining strips cut 52-31/2"x 61/2" strips for Sashing Units 1 and 3 and 8-3¹/₂"x 9¹/₂" strips for Sashing Unit 2.





CONSTRUCTION

Building 9-Patch Blocks

Step 1

Sort and label the various 25%"xWOF strips needed for each of the Strip Sets. Strip Sets A and B are used in 9-Patch Unit 1 Strip Sets C and D are used in 9-Patch Unit 2

Strip Set A –18 units Need 4F1 strips and 2F3 strips



Strip Set B –36 units Need 3F2 strips and 6F3 strips

Strip Set C –18 units Need 4F2 strips and 2F6 strips

Strip Set D –36 units Need 3F1 strips and 6F6 strips

F1 F6

F6

Making the Strip Sets

Strip Set A – Make 2

Using a ¹/₄" seam stitch 2 F1 strips and 1F3 strip together. Press seams toward arrows.





Strip Set B – Make 3

Using a ¹/₄" seam stitch 3 F2 strips and 6F3 strip together. Press seams toward arrows.



Make 3 strip sets Cut a total of 36-25%" segments

Assemble 9-Patch 1 Blocks – Make 18



Stitch strip sets together using a $\frac{1}{4}$ " seam Press seams open.



Blocks should measure 67/8" x 67/8" with seams. Press seams open.

Making the Strip Sets

Strip Set C – Make 2

Using a ¹/₄" seam stitch 4F2 strips and 2F6 strip together. Press seams toward arrows.



Make 2 strip sets Cut a total of 18-2%" segments

Strip Set D – Make 3

Using a ¹/₄" seam stitch 3 F2 strips and 6F3 strip together. Press seams toward arrows.



Make 3 strip sets Cut a total of 36-25%" segments

Assemble 9-Patch 2 Blocks – Make 18



Stitch strip sets together using a $1\!\!/\!\!4''$ seam Press seams open.



Blocks should measure $67\!\!/\!\!/ \slash seams$ with seams. Press seams open.



Add Corner Triangles to 9-Patches

Need: 72 F1(red) half square triangles and 72 F2 (green) half square triangles

Fold triangles in half to find center of long side of each triangle. Find center of 9-patch block. Match and stitch green triangle to green square and red to red. Press seams toward triangles. Square blocks to measure $9\frac{1}{2}$ "x $9\frac{1}{2}$ " with seams.

9-Patch 1 Make 18





Square blocks to measure 91/2"x 91/2" with seams.

Building Sashing Units 1, 2, 3

Need: From F5

96-2"x 2" squares for corner triangles for Sashing Units 2 and 3.

And 5-3¹/₂"x 3¹/₂ sashing star centers.

From F6

52-3¹/₂"x 3¹/₂ squares for sashing squares **From F7**

104-2"x 2" squares for corner triangles for Sashing Units 1 and 3.

From F8

104-2"x 2" squares for corner triangles for Sashing Units 1 and 3.

12-3¹/₂"x 3¹/₂ squares for sashing star center squares 52-3¹/₂"x 6¹/₂ rectangles for Sashing Units 1 and 3. 8-3¹/₂"x 9¹/₂ rectangles for Sashing Unit 2.

Jnit should measure 3%"x 9%" with seams.



Trim seam to ¼". Press toward corner. Repeat steps to add additional corners to background square if needed.



Sashing Unit 1– Make 12



Needed for each unit: F8 1-3½"x6½" rectangle and 2-2"x 2" squares for corners F6 1-3½"x 3½" center square F7 2-2"x 2" squares for corners

Sashing Unit 2– Make 8



Needed for each unit: F8 1-31/2"x 91/2" rectangle F5 2-2"x2" squares for corners

Sashing Unit 3– Make 40



Needed for each unit: F8 1-3½"x6½" rectangle and 2-2"x 2" squares for corners F6 1-3½"x 3½" center square F5 2-2"x 2" squares for corners F7 2-2"x 2" squares for corners



Assemble Quilt Sections _____

This quilt is assembled in 9-4 block sections. The 4 pieced blocks within each section are an assortment of 9-Patch 1 and 9-Patch 2 blocks.



Section 1- Make 2

Unit 2

Note: A large red triangle should always point to the center of each section.

- Step 1: Stitch a 9-Patch 1 block to the left side of a Unit 1Sashing. Press seam toward block.
- Step 2: Stitch a 9-Patch 2 block to the right side of a Unit 1Sashing. Press seam toward block.
- Step 3: Noting placement of the F7 triangles, stitch a Unit 1 Sashing to the left side of the F8 3½"x 3½"center square. Press seam toward center. Then stitch a Unit 3 Sashing to the opposite side of the center square. Note placement of the F5 triangles. Press seam toward center.
- Step 4: Stitch a 9-Patch 2 block to the left side of a Unit 3 Sashing. Note placement of the F5 triangles Press seam toward block.
- Step 5 : Stitch a 9-Patch 1 block to the right side of a Unit 3 Sashing. Press seam toward block.
- Step 6 : Join rows and sashing. Press seam toward sashing. Section should measure 21¹/₂"x 21¹/₂" with seams.



Section 2-Make 4

Note: A large red triangle should always point to the center of each section.

- Step 1: Stitch a 9-Patch 2 block to the left side of a Unit 1Sashing. Press seam toward block.
- Step 2: Stitch a 9-Patch 2 block to the right side of a Unit 1Sashing. Press seam toward block.
- Step 3: Noting placement of the F8 triangles, stitch a Unit 1 Sashing to the left side of the F8 3½"x 3½"center square. Press seam toward center. Then stitch a Unit 3 Sashing to the opposite side of the center square. Note placement of the F5 triangles. Press seam toward center.
- Step 4: Stitch a 9-Patch 1 block to the left side of a Unit 3 Sashing. Note placement of the F5 triangles Press seam toward block.
- Step 5 : Stitch a 9-Patch 1 block to the right side of a Unit 3 Sashing. Press seam toward block.
- Step 6 : Join rows and sashing. Press toward sashing. Section should measure 211/2"x 211/2" with seams.

moda

ASSEMBLE QUILT SECTIONS _



Section 3 - Make 2

Note: A large red triangle should always point to the center of each section.

- Step 1: Stitch a 9-Patch 2 block to the left side of a Unit 1Sashing. Press seam toward block.
- Step 2: Stitch a 9-Patch 2 block to the right side of a Unit 1Sashing. Press seam toward block.
- Step 3: Noting placement of the F7 triangles, stitch a Unit 1 Sashing to the left side of the F8 3½"x 3½"center square. Press seam toward center. Then stitch a Unit 1 Sashing to the opposite side of the center square. Note placement of the F7 triangles. Press seam toward center.
- Step 4: Stitch a 9-Patch 1 block to the left side of a Unit 3 Sashing. Note placement of the F5 triangles. Press seam toward block.
- Step 5: Stitch a 9-Patch 2 block to the right side of a Unit 3 Sashing. Press seam toward block.
- Step 6: Join rows and sashing. Press toward sashing. Section should measure 21¹/₂"x 21¹/₂" with seams.





Center Section 4 - Make 1

Note: A large red triangle should always point to the center of each section.

- Step 1: Stitch a 9-Patch 1 block to the left side of a Unit 3 Sashing. Press seam toward block. Note placement of the F5 triangles.
- Step 2: Stitch a 9-Patch 1 block to the right side of a Unit 3 Sashing. Press seam toward block.
- Step 3: Noting placement of the F7 triangles, stitch a Unit 3 Sashing to the left side of the F5 3½"x 3½"center square. Press seam toward center. Then stitch a Unit 3 Sashing to the opposite side of the center square. Note placement of the F7 triangles. Press seam toward center.
- Step 4: Stitch a 9-Patch 1 block to the left side of a Unit 3 Sashing. Note placement of the F5 triangles Press seam toward block.
- Step 5 : Stitch a 9-Patch 1 block to the right side of a Unit 3 Sashing. Press seam toward block.
- Step 6 : Join rows and sashing. Press toward sashing. Section should measure 211/2"x 211/2" with seams.

Assemble Joining Sashings _

With the remaining sashing units assemble the following Joining Sashings.









Sashing 2 F7 Sashing 3 F8 Sashing 3 F5 Sashing 3 F8 Sashing 3 F7 Sashing 2



Row 1: Stitch Section 1 to the left side of Section Sashing 1. The Sashing 2 section in Section Sashing 1 should be positioned at the top of the row. Note direction of arrow. Press seams toward block.

Add Section 2 to the right side of a Section Sashing 1. the sashing section without triangles should be at the top of the row. Note direction of arrow. Press seams toward block

Stitch Section 2 to the left side of a Section Sashing 1. The Sashing 2 section in Section Sashing 1 should be positioned at the top of the row. Press seams toward block.

Stitch a Row Sashing unit to the bottom of Row 1. Press seam open.

Row 2: Stitch Section 2 to to the left side of Section Sashing 2. Press seams toward block.

Add Section 4 to the right side of a Section Sashing 2 Press seams toward block.

Add Section Sashing 2 to the right side of Section 4 Press seams toward block.

Stitch Section 2 to right side of Section Sashing 2 Note direction of arrow. Press seams toward block. Stitch the second Row Sashing unit to the bottom of Row 2. Join Rows 1 and 2. Press seams open.



oda m

Assemble Quilt – cont.

- Row 3: Stitch Section 3 to the left side of Section Sashing 1. Note direction of F7 triangles. Press seams toward block.
 - Add Section 2 to the right side of a Section Sashing 1. the sashing section without triangles should be at the bottom of the row. Note direction of arrow. Press seams toward block
 - Stitch Block 2 to the left side of a Section Sashing 1. Note direction of arrow. Press seams toward block. Add Section 2 to the right side of a Section Sashing 1. the sashing section without triangles should be at the bottom of the row. Note direction of arrow. Press seams toward block

Stitch Section 2 to the left side of Section Sashing 1. Note direction of F7 triangles. Press seams toward block.

Add Section 1 to the right side of a Section Sashing 1. the sashing section without triangles should be at the bottom of the row. Note direction of arrow. Press seams toward block.

Stitch Row 3 to bottom of Row Sashing unit to complete the quilt top. Press seam open.

Quilt should measrue 70"x70" with seams.

FINISHING -

- 1. Using a diagonal seam, join binding strips end to end. Press seams open. Fold prepared strip in half wrong sides together and press to make the binding.
- 2. Layer, Quilt, and Bind.

Rose by Jo Morton

Finished Size: 70"x70"

Fabric Requirements:













moda